

RF600 SHF1
75 Ohm Coaxial Cable



Application

Cable Design

Conductor	Copper Clad Aluminium nom. 2,74 mm
Dielectric	Foam PE nom. 11,56 mm
Outer Conductor	Bonded aluminium foil nom. 11,71 mm
Braid	Tinned Copper Braid nom. 12,45 mm
Outer Jacket	FR-LSZH SHF-1 < UV Resistant >
Diameter	Ø 14,99 ± 0,5 mm

RF600 SHF1
75 Ohm Coaxial Cable

Environmental and Fire Characteristics

Degree of acidity of gases	IEC 60754-1/2
Halogen acid gas	IEC 60754-1/2
Smoke Emission	IEC 61034-1/2
Flame retardant	IEC 60332-1
Fire retardant	IEC 60332-3-22 Cat.A
UV resistant	UL 1581

Performance

Impedance	75 ± 3	Ohm
Capacitance	51,1	pF/m (nominal)
Velocity ratio	87	%
Insulation resistance	> 5000	MOhm.km
Inner conductor resistance	4,69	Ohm/km
Outer conductor resistance	5,74	Ohm/km
Storage Temperature	-20 to +60	°C
Installation Temperature	0 to +50	°C
Operating Temperature	-40 to +85	°C
Min. Bend Radius Installation	38,1	mm
Min. Bend Radius Operating	38,1	mm

RF600 SHF1
75 Ohm Coaxial Cable

Attenuation

Frequency	MHz	30	50	150	220	450	900	1500	1800	2000	2500
Typical	dB100ft	0,55	0,57	0,87	0,89	1,49	2,47	3,34	3,50	3,70	4,20
Max.	dB100ft	0,58	0,67	1,10	1,20	1,80	2,60	3,50	3,90	4,10	4,60

Other standards of reference

IEC 60092-370	Electrical installations in ships: Guidance on the selection of cables for telecommunication and data.
DNV TAP 827.10/20	Type Approval Program - coaxial cables
MIL-C-17	General specification for radio frequency coaxial cables
IEC61196-1	Coaxial communication cables
EN 50290-2-23	Insulation materials for telecommunication cables

Specification

Part Number	Type
RF600 75 SHF1	75 Ohm Coaxial Cable for LMR (Land Mobile Radio) communications in marine and off-shore environments.